



BETTER SOUND. LESS NOISE. MORE CONCENTRATION.

BENEFITS

- Keep callers in the zone with the only DECT™ headset featuring active noise canceling (Savi 8220)
- Ensure that sensitive conversations stay private—headsets are DECT™ security certified by the DECT™ forum using the latest security standards
- Tune out office noise and nearby conversations with noise canceling microphone plus close conversation limiting
- Get crystal clear audio with the latest DECT™ technology supports wideband audio without impacting user density

SAVI 8200 OFFICE AND UC SERIES

Noisy workspace? No problem. Invest in getting more done with the Savi 8200 Office and UC Series headsets. Tune out nearby noise and keep every conversation secure, private, and clear with close conversation limiting noise cancellation. Give your employees the freedom to roam plus long talk time—the unique hot swappable battery option even makes it unlimited.* With multiple wearing styles, you can let every member of your team pick their favorite or keep their options open with the convertible model. Wherever you work, the Savi 8200 Office and UC Series helps you be at your best all day long.

- Choice of wearing styles, including the 3-in-1 convertible options (Savi 8240/8245)
- Line of sight range up to 590 feet/180 meters
- Up to 13 hours talk time with over-the-head (OTH) models (Savi 8210/8220)
- Up to 7 hours talk time (Savi 8240) or unlimited talk time with the Savi 8245 model

*Savi 8245



SAVI 8200 OFFICE AND UC SERIES



SAVI 8240/8245

SPECIFICATIONS

TALK/STANDBY TIME

- Up to 13 hours talk, up to 50 hours standby (Savi 8210 and Savi 8220)
- Up to 7 hours talk, up to 30 hours standby (Savi 8240) Unlimited talk and standby (Savi 8245)

HEADSET WIRELESS RANGE

- Line of sight: Up to 590 ft/180 m; Typical office environment: Up to 180 ft/55 m

BATTERY CAPACITY

- 490 mAh (Savi 8210), 700 mAh (Savi 8220), 140 mAh (Savi 8240/8245)

BATTERY TYPE

- Rechargeable, replaceable, lithium ion polymer

CHARGE TIME

- Three hours

WIRELESS TECHNOLOGY

- DECT™ 6.0 (Savi 8200 UC) and Bluetooth v4.2 (Savi 8200 Office)

AUDIO PROFILES (SAVI 8200 OFFICE)

- Advanced Audio Distribution Profile (A2DP); AVRCP; Bluetooth Hands-Free Profile (HFP); Bluetooth Headset Profile (HSP)

CODECS

- G726, G722, Broadvoice32, OPUS/CELT 16kS, OPUS/CELT 48kS

RECEIVE AUDIO PERFORMANCE

- Active noise canceling (ANC) (Savi 8220)

RECEIVE FREQUENCY RESPONSE

- Wideband: 100–6800 Hz; Multimedia 20 Hz–20 kHz

HEARING PROTECTION

- SoundGuard DIGITAL: protects against sound levels above 118dBA; G616 anti-startle (during calls) detects and eliminates any large sudden increase in signal level; Time-weighted average prevents average daily noise exposure from exceeding 85dBA*
*Requires Plantronics Hub software to enable SoundGuard DIGITAL features.

MICROPHONE AND TECHNOLOGY

- Noise canceling with close conversation limiting

WEIGHT

- Savi 8210 (Mono): 115 g; Savi 8220 (Stereo): 160 g; Savi 8240/8245 (Convertible): 21 g (over-the-ear)

CALL CONTROLS

- Call answer/end, mute, volume +/-, ANC on/off (Savi 8220), power on/off

VOICE AND OTHER ALERTS

- Multiple voice prompts

APPLICATIONS SUPPORTED

- Plantronics Hub application on desktop

PLANTRONICS MANAGER PRO SUITES SUPPORTED

- See Software and Services

LEARN MORE

For more information on Savi 8200 Office and UC Series visit

plantronics.com/us/en/product/savi-8200

DATA SHEET

Polycom® EagleEye™ Mini Camera

Compact camera with big time performance—making your favorite Polycom audio meetings more meaningful

Video collaboration improves our communications and decision-making abilities. Nonverbal cues, such as body language and facial expressions, add another dimension to communications. When people can see each other, they feel more emotionally connected and engaged.

Complements Polycom Audio Solutions

Polycom audio innovations have been leading the market for over 25 years. Our mission is to enhance the power of communication. There is only one way to improve our audio—add video. The EagleEye Mini USB camera can easily be added to Polycom Trio conference phones*, VVX® 501 and 601 desktop phones and the Polycom VoxBox USB portable speakerphone.

Business-class HD video

This feature-rich camera has been engineered for business-class performance in personal and small room environments. Some of the many highlights include high definition 1080p video, electronic pan, tilt and 4x zoom for an image that remains at the highest capable resolution even when it is fully zoomed. Additionally, EagleEye Mini brings forth true color hue saturation, backlight compensation, and autofocus optimized for smaller environments so you can be sure you will experience accurate, sharp, life-like images. As if all this isn't enough, EagleEye Mini supports simulcast streams so far-end participants will enjoy the highest resolution their endpoint can accommodate. When not in use, the integrated privacy shutter prevents unintentional use of your camera for added security.

Ideal for personal and small room environments

Today, people work in a variety of spaces—from a desk, a huddle room or on the go at the local café, hotel or shared workspace, bring along EagleEye Mini and Polycom VoxBox and work anywhere. The EagleEye Mini camera mounts on the wall or on the top or the bottom of a display, for comfortable eye-contact for everyone in the room.

Skype for Business Certified

EagleEye Mini is a certified USB camera for Skype for Business video calls ensuring the highest quality meeting experience for your team and remote participants.

It's a compact camera with big time performance.




Benefits

- Instantly add business quality video collaboration to your favorite Polycom audio solutions
- A compact and cost-effective video solution for the desktop, huddle room or on the go
- Security features including integrated privacy shutter and video mute/unmute LED indicator
- Simulcast video streams for remote participants best possible video experience

*Requires Polycom Trio Visual+

Mounting Kit configuration options


Top Mount




Bottom Mount



Wall Mount



VVX Mount



Product specifications

EagleEye Mini features

- Integrated privacy shutter
- Mechanically adjustable tilt
- Plug and Play setup
- Uncompressed local video loopback
- Normal, full, crop video screen modes
- Adjustable levels and frame rate
- Anti-flicker compensation
- 2 color/4 state status LED

Video standards

- H.264 AVC, H.264 high profile encoding
- H.264 SVC for Skype for Business encoding
- RGB and YUV raw video

Bandwidth

- 280 Mbps max transmit bitrate

Content video resolution

- 24-bit true color
- Supports up to 1080p @ 30fps transmit video (H.264)
- Multicast video streams

Camera

- f/2.0 aperture
- 4 mega pixel sensor
- Vertical tilt angle adjustable from +6° (up) to -22° (down)
- 73.7° HFoV/ 82°DFoV
- Automatic exposure and white balance
- Autofocus, 8cm-infinity
- 4x electronic zoom (1.4x lossless)

Complements the following Polycom audio solutions:

- Polycom VVX® 601 v 5.87.1 or above
- Polycom VVX® 501 v 5.8.1 or above
- Polycom Trio™ 8500* v 5.7.1 or above
- Polycom Trio™ 8800* v 5.7.1 or above
- Polycom® RealPresence® Desktop for Windows® and Mac® v 3.9.0 or above
- Polycom VoxBox v 1.0.1 or above

*Requires Polycom Trio™ Visual+

Supported video communication clients

- Polycom RealPresence Desktop
- BroadSoft UC-One Communicator
- Skype for Business (certified by Microsoft)
- Zoom

Camera firmware updates

The EagleEye Mini USB camera receives firmware updates through software updates for the connected VVX business media phone or Polycom Trio system. When using the EagleEye Mini USB camera with a Windows or Mac computer, users can update the camera's firmware using the Polycom® Companion application, which users can download from [Polycom Support](#).

Interface

- USB 2.0 (UVC 1.5 and UVC 1.1 compliant)

Power

- 5V @ <500mA via USB port

Approvals

- FCC Part 15 (CFR 47) Class B
- ICES-003 Class B
- EN55032 Class B
- CISPR32 Class B
- VCCI Class B
- EN55024

- EN61000-3-2; EN61000-3-3
- Korea KCC
- ROHS compliant
- Russia EAC
- Australia C Tick

Safety

- UL 60950-1
- UL 62368-1
- CE Mark
- CAN/CSA-C22.2 No. 60950-1-03
- EN 60950-1
- EN 62368-1
- IEC 60950-1
- IEC 62368-1
- AS/NZS 60950-1

Operating Conditions

- Temperature: +32 to 104°F (0 to 40°C)
- Relative Humidity: 5% to 95%, noncondensing

Storage Temperature

- -40 to +160°F (-40 to +70°C)

Country of Origin

- China

Warranty

- One (1) year

Part numbers

- EagleEye Mini Camera: 2200-85010-001
- EagleEye Mini Camera w/mounting kit: 7200-84990-001

Learn more

Visit www.polycom.com/eagleeye to learn more about the EagleEye Mini Camera and other EagleEye products.